

## About

|                     |                       |          |
|---------------------|-----------------------|----------|
| Type of manufacture | Woven                 | ISO 2424 |
| Width               | 400 cm                | ISO 3018 |
| Type of surface     | Loop pile             | ISO 2424 |
| Pile material       | 100% undyed wool      | ISO 2424 |
| Backing             | Cottonback            | ISO 2424 |
| Pile weight         | 995 g/m <sup>2</sup>  | ISO 2424 |
| Total weight        | 2000 g/m <sup>2</sup> | ISO 8543 |
| Pile height         | 4,0 mm                | ISO 1766 |
| Total height        | 7,4 mm                | ISO 1765 |

## Application

|                               |                                             |                                                                                                                                                                             |                         |
|-------------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Use classification            | 23 residential use / 32 commercial use      |   | EN 1307 / ISO 10361     |
| Suitability for use on stairs | Suitable for residential and commercial use |                                                                                        | EN 1307 / ISO 12951     |
| Suitability for castor chair  | Suitable for residential and commercial use |                                                                                        | EN 1307 / ISO 4918      |
| Antistatic behaviour          | ≤ 2.0 kV at 25%RH                           |                                                                                        | ISO 6356                |
| Thermal resistance            | 0.09 m <sup>2</sup> K/W                     |                                                                                        | EN 12667                |
| Burning behaviour             | C <sub>fl</sub> -s1                         |                                                                                        | EN 13501-1 / ISO 9239-1 |
| Colourfastness to light       | ≥ 4                                         |                                                                                        | EN 1307 / ISO 105-B02   |
| Impact sound insulation       | Δ L <sub>w</sub> 25 dB                      |                                                                                        | EN 717-2 / ISO 10140-3  |
| Comfortclass                  | LC1                                         |                                                                                        | EN 1307 / EN 8543       |
| Slip resistance               | DS                                          |                                                                                        | EN 14041 / EN 13893     |