












## About

Type of manufacture	Woven	ISO 2424
Width	500 cm	ISO 3018
Type of surface	Cut pile	ISO 2424
Pile material	100% PA 6 ECONYL®	ISO 2424
Backing	Cottonback	ISO 2424
Pile weight	2800 g/m <sup>2</sup>	ISO 2424
Total weight	3600 g/m <sup>2</sup>	ISO 8543
Pile height	9,0 mm	ISO 1766
Total height	12,0 mm	ISO 1765

## Application

Use classification	23 residential use / 31 commercial use		EN 1307 / ISO 10361
Suitability for use on stairs	Suitable for residential use		EN 1307 / ISO 12951
Suitability for castor chair	Not suitable		EN 1307 / ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25%RH		ISO 6356
Thermal resistance	0.13 m <sup>2</sup> K/W		EN 12667
Burning behaviour	C <sub>fl</sub> -s1		EN 13501-1 / ISO 9239-1
Colourfastness to light	≥ 6		EN 1307 / ISO 105-B02
Impact sound insulation	Δ L <sub>w</sub> 25 dB		EN 717-2 / ISO 10140-3
Comfortclass	LC5		EN 1307 / EN 8543
Slip resistance	DS		EN 14041 / EN 13893