



About

Type of manufacture	Woven	ISO 2424
Width	400 cm	ISO 3018
Type of surface	Loop pile	ISO 2424
Pile material	100% PA 6 ECONYL®	ISO 2424
Backing	Actionback	ISO 2424
Pile weight	600 g/m ²	ISO 2424
Total weight	2100 g/m ²	ISO 8543
Pile height	3,8 mm	ISO 1766
Total height	4,5 mm	ISO 1765

Application

Use classification	23 residential use / 33 commercial use		EN 1307 / ISO 10361
Suitability for use on stairs	Suitable for residential and commercial use		EN 1307 / ISO 12951
Suitability for castor chair	Suitable for residential and commercial use		EN 1307 / ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25%RH		ISO 6356
Thermal resistance	0.06 m ² K/W		EN 12667
Burning behaviour	C _{fl} -s1		EN 13501-1 / ISO 9239-1
Colourfastness to light	≥ 5		EN 1307 / ISO 105-B02
Impact sound insulation	Δ L _w 16 dB		EN 717-2 / ISO 10140-3
Sound absorption	0,15 α _w		ISO 354
Comfortclass	LC1		EN 1307 / EN 8543
Slip resistance	NPD		EN 14041 / EN 13893

 creative colour concept: available in custom colours from 400 m².

