













## About

Type of manufacture	Tufted	ISO 2424
Width	400 cm	ISO 3018
Type of surface	Cut/Loop pile	ISO 2424
Pile material	100% PA	ISO 2424
Backing	Actionback	ISO 2424
Pile weight	1075 g/m <sup>2</sup>	ISO 2424
Total weight	1950 g/m <sup>2</sup>	ISO 8543
Pile height	5,0 mm	ISO 1766
Total height	6,5 mm	ISO 1765

## Application

Use classification	23 residential use / 32 commercial use		EN 1307 / ISO 10361
Suitability for use on stairs	Suitable for residential use		EN 1307 / ISO 12951
Suitability for castor chair	Suitable for residential use		EN 1307 / ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25%RH		ISO 6356
Thermal resistance	0.12 m <sup>2</sup> K/W		EN 12667
Burning behaviour	C <sub>fl</sub> -s1		EN 13501-1 / ISO 9239-1
Colourfastness to light	≥ 5		EN 1307 / ISO 105-B02
Impact sound insulation	Δ L <sub>w</sub> 20 dB		EN 717-2 / ISO 10140-3
Comfortclass	LC4		EN 1307 / EN 8543
Slip resistance	DS		EN 14041 / EN 13893

 creative colour concept: available in custom colours from 400 m<sup>2</sup>.

